

LIVEMAKER 1021 MIX

900W 2.1 PORTABLE PA SYSTEM WITH 8-CH MIXER, EFFECT AND BLUETOOTH

The LIVEMAKER 1021 MIX, 900W 2.1 PA system, is designed as a compact system for live and educational purposes. It integrates an 8-channel mixer with Digital Effects and Bluetooth, three Class-D amplifiers with switching power supply, for 900W total peak power, a generous 10" subwoofer and two satellites with a 6.5" woofer and 1" compression driver. It represents the perfect answer to those who need a professional sound system, but have problems of space, move with not very big cars or vans, and have a lot of audio sources to be connected. Not only, but they also need a professional reverb and, if necessary, want to connect a mobile phone, a tablet or a computer to play their play-lists. Both the subwoofer and the two tops are equipped with 36mm hole for pole or tripod. The reinforced MDF cabinets are robust, lightweight and finished with anti-scratch paint, to make them resistant to the rigors of the stage.

LIVEMAKER 1021 MIX

[d0571097-c53e-4679-9404-6184d863e93f.jpg](#)

[20c624e6-1626-41fe-a576-6417ed0a9ddb.jpg](#)

[7960e503-fb2d-48b8-a32f-15fe](#)

[71ea04b6-78cb-4bc2-9bf4-57c8f437d2d0.jpg](#)

[7f36284b-b7e0-414c-a085-3e20e17e9c2f.jpg](#)

[456b71a0-a97d-4c3d-bbfe-61c5](#)

PRODUCT DETAILS

KEY FEATURES

2.1 Compact PA System with 2 passive satellites and 1 active subwoofer

2 passive Tops with reinforced MDF cabinet, featuring 6.5" and 1" silk cloth dome driver

Active bass-reflex subwoofer with reinforced MDF enclosure, featuring a 10" woofer for up to 123dB sound pressure

8 Channel mixer with 4 MIC Inputs, 1 Stereo Line Input, 1 Stereo Bluetooth Input

2-Band EQ, 16 Digital Effects (Mic channels only)

900W Peak power class-D amplifier with high-efficiency, low-heat dissipation switching power supply

Balanced MIC/Line Inputs and Balanced Outputs

Standard M20mm pole mount adapter over the sub top and D36mm under the two satellites

2 handles on subwoofer (1 on each side)

1 Rear handle on each top

SPECIFICATIONS

System Max SPL	124 dB
System Frequency Response	45 Hz-20 kHz
Satellite Power RMS / Peak	150W / 300W (each)
Satellite Frequency Response	90 Hz-20 kHz
Satellite Sensitivity (1W@1m)	90 dB
Satellite Max. SPL (@1m)	111 dB
Satellite nominal Impedance	8 ohms
Satellites Input Connectors	2 x Speakon
Satellite LF	1 x 6.5" with 1.5" voice coil
Satellite HF	1 x 1" voice silk cloth dome
Satellite Crossover Frequency	3 kHz, 12 dB/octave
Speaker Pole Adapter	Ø36mm
Satellite Size (WxHxD)	225 x 346 x 215 mm
Satellite Weight	6.4 kg
Inputs	MIC XLR, 6.3mm jack, RCA
EQ Control	Low
Bluetooth connection distance	>6m
Subwoofer amplifier	1 x 300W RMS @ 4ohms
Satellites amplifier	2x 150W RMS @ 8ohms
LF driver	10" with 2.5" voice coil
Sub Frequency response	45 Hz-150 Hz
Sub Sensitivity (1m/1W)	90 dB
Sub Max. SPL (@1m)	123 dB
Mains	AC 230V 50Hz (Fuse
Subwoofer Size (WxHxD)	340 x 429 x 460 mm
Subwoofer Net Weight	22 kg
Housing material	MDF + Anti-scratch Printing (Black finish)

Handles

2 on subwoofer (1 on each side); 1 on rear side of each top

Pole Mount Adapter

Standard M20