

# LIVEMAKER 12 PRO


## ACTIVE 2-WAY COLUMN SYSTEM WITH DSP


LiveMaker 12 Pro is a professional Active 2-Way Column System designed to deliver exceptional performance, versatility, and reliability for live sound applications. With its powerful built-in amplifier delivering 600W / 400W RMS for LF/HF (1200W / 800W Peak), the system is engineered to provide crystal-clear audio and high dynamic range.

The system features a 12" low-frequency woofer, four 3.5" full-range mid-frequency drivers, and a 1" high-frequency compression driver, ensuring a balanced and full-spectrum sound. The integrated DSP processor offers 4 presets tailored for different scenarios: Flat, Live, Loudness, and DJ. To ensure durability and seamless operation, the DSP includes limiter, overcurrent, and thermal protections.

In addition to its professional-grade capabilities, the LiveMaker 12 Pro features a lightweight and ergonomic design that makes it exceptionally easy to transport and setup. Its portability ensures that users can quickly adapt to various venues and events, making it a practical solution for all mobile applications. The subwoofer cabinet is designed to house all system components inside it (column with its bag, pole and connection cables with their bag) while minimizing bulk and limiting the risk of damage to parts during transport.

Connectivity is also versatile, with an XLR and 1/4" jack combo input, 3-pin XLR Mix Output for chaining, and Bluetooth with TWS functionality for wireless audio streaming and stereo pairing. Whether for live performances, DJs, or professional events, the LiveMaker 12 Pro combines power, precision, and practicality, making it an ideal choice for modern audio professionals.





## HIGHLIGHTS



### DESIGNED FOR EXCEPTIONAL PERFORMANCE

The system features a 12" woofer that functions as a subwoofer. The column includes four 3.5" full-range drivers and a 1" compression driver with a symmetric waveguide. The result is a balanced and rich sound across the entire frequency spectrum.

### COMPLETE CONTROL WITH SAFETY

The integrated DSP offers four optimized presets for different scenarios: Flat, Live, Loudness, and DJ. Additionally, to ensure maximum reliability, the DSP includes protections against signal clipping, overcurrent, and overheating. Simply select the desired program, and the internal processor takes care of the rest.



### COMPACT AND HIGHLY PORTABLE



The subwoofer cabinet is designed to house all system components (column with its bag, pole, and connection cables – all also with their own bag), minimizing the overall size and reducing the risk of damage to parts during transport.

## PRODUCT DETAILS

### KEY FEATURES

Active subwoofer with integrated DSP and passive Column Speaker

600W (LF) / 400W (HF) RMS and 1200W / 800W Peak Class-D Power Amplifier

1 x 12" Woofer (Subwoofer), 4 x 3.5" Full-range Drivers, and 1 x 1" Compression Driver (Column)

4 DSP Presets (Flat, Live, Loudness, DJ)

XLR & 1/4" Jack Combo Input and XLR Mix Output for daisy-chaining

Bluetooth with TWS functionality for wireless streaming and pairing.

Lightweight and ergonomic design for easy transport and setup.

Adjustable M20 to 35mm pole included

## SPECIFICATIONS

<b>Built-in Amplifier LF/HF</b>	600 / 400W Nominal Power - 1200 / 800W Peak Power
<b>Frequency Response @ -6dB</b>	40Hz - 20kHz
<b>Maximum SPL (Nominal/Peak)</b>	125dB - 129dB
<b>Dispersion HxV</b>	110° x 30°
<b>Crossover Frequency</b>	180 Hz
<b>Low Frequency Woofer</b>	12" - 3.0" v.c., 4 Ohm
<b>MF Driver</b>	4 x 3.5" full-range, 1.0" v.c., 8 Ohm
<b>HF Compression Driver</b>	1 x 1", 1.0" v.c., 8 Ohm
<b>DSP Presets</b>	4 presets (Flat, Live, Loudness, DJ)
<b>Connectors</b>	Input (XLR & 1/4" jack Combo), Mix Out (3-pin XLR), Speaker Out (Speakon), Power Input (VDE)
<b>Sub/Column Enclosure Material and Thickness</b>	Plywood-12mm
<b>Sub/Column Grille Material and Thickness</b>	Steel-1.2mm
<b>Pole Mounting</b>	36mm hole on bottom (column side), M20 (sub side)
<b>Accessories</b>	M20 to 36mm Adjustable Pole with bag, 1.4m Speaker cable, 2x ABS rings
<b>Handles</b>	1 on Sub top; 1 on Column Rear
<b>Satellite Dimensions (WxDxH)</b>	115 x 160 x 545 mm
<b>Subwoofer Dimensions (WxDxH)</b>	385 x 510 x 590 mm
<b>Packing Dimensions (WxDxH)</b>	425 x 630 x 550 mm
<b>Product Weight</b>	26.5 kg
<b>Packing Weight</b>	28.5 kg