

VOXTAKER 100 USB

CONDENSER STUDIO MICROPHONE WITH CARDIOID POLAR PATTERN AND USB INTERFACE

VoxTaker 100 USB is a plug and play condenser studio recording microphone, without having to install any driver. Like the VoxTaker 100, it is a professional microphone featuring true condenser capsule with cardioid polar pattern. It can be used with confidence in a variety of professional applications, such as recording studios, broadcasting, podcasting, and stage performances just connecting a USB cable. It is compatible with all recording software and ASIO audio drivers. It uses high-performance USB chip technology and high-quality single-point capacitive transducers. That's why the VoxTaker 100 USB has very low self-noise and high output to reproduce even the subtle sound and fulfil the requirement of high sound quality for broadcasting and recording. The package includes Shock-Mount, Pop Filter and USB cable, all inside a plastic case.

VOXTAKER 100 USB

8e48dd21-45d8-4205-b80b-b26466707da2.jpg

ea662f4e-874b-4a02-84be-db8db24bd13b.jpg

326b44f7-aa94-43f0-a6b1-e4

PRODUCT DETAILS

KEY FEATURES

Professional Pressure Gradient Transducer

Cardioid Polar Pattern

High Quality FET Preamp

Strong Output Signal without Distortion

High-speed AD/DA conversion technology

44.1/48 kHz Sample Frequency

16 Bit Resolution

USB 2.0 Plug and Play Operation

Maximum compatibility with all Operative Systems without any drivers

Low Power Consumption

High Absorption Shock-mount

Stylish and Innovative Pop Filter

Package includes Plastic Case and USB cable

SPECIFICATIONS

Element	16mm high-sensitivity condenser capsule
	Cardioid Polar Pattern
Frequency Response	30Hz -20kHz
Sensitivity	-34dB (0dB = 1V/Pa at 1kHz)
Max Input SPL	130dB (at 1kHz 1% T.H.D.)
	16bit A/D-D/A conversion resolution
	Stereo ADC/DAC operation
	USB 2.0 transceiver
ADC sampling frequency	8k, 11.025k, 16k, 22.05k, 32k, 44.1k, 48kHz
	ADC THD+N = 0.01%
	ADC S/N Ratio = 89dB
	ADC Dynamic Range = 89dB
DAC frequency	32k, 44.1k, 48kHz
	DAC THD+N = 0.005%
	DAC S/N Ratio = 96dB
	DAC Dynamic Range = 93dB
Stereo output power	400mW
Microphone Size (WxHxD)	188x50x50 mm
Microphone Weight	252 g
Case Size (WxHxD)	340 x 280 x 90 mm
Package Weight (Mic., case and accessories)	1.5kg