

HYPER TOP 8A

480W 8" Polypropylene bi-amped active speaker

HYPER series is the result of years of experience gathered by Soundsation in Portable Sound systems. This speaker line is built with a sturdy, lightweight and stylish polypropylene enclosure with full metal grille and acoustic foam to protect the transducers. The cutting-edge design, according to latest industry standard, offers both a great look and an optimal sound quality. All models are equipped with a Class D amp and switching power supply to deliver massive power with great efficiency and light weigh. (with the exception of the 6"). MIC and Line inputs to connect all major input sources, being microphones, mixers or media players. Featuring four M8 flying points distributed on each side, 1 handle on top and a standard D36mm pole mount hole it is ideal for both fixed installation or portable applications.



KEY FEATURES

2-Way bi-amped Active Speaker

High resonance, sturdy and lightweight polypropylene cabinet with full metal grille and foam soundproof material

2 Class D amplifiers 480W (432W+48W)

8" woofer and 1" driver

Microphone/line inputs XLR + jack jack ¼"

XLR output link out

Volume and equalization Hi/LOW controls

Suited for stage monitor use at 30°/45°

Top handle for easy carrying

36mm pole mount

4 M8 flying points, one each side

Dimensions (WxHxD)	270 x 495 x 270 mm
--------------------	--------------------

Weight	7,2 Kg
--------	--------

MORE SPECIFICATIONS

2-Way active bi-amped speaker

Woofer	8" with 1.5" voice coil
--------	-------------------------

Compression driver	1" voice coil, 1" throat
--------------------	--------------------------

Horn	90° x 60°, symmetric
------	----------------------

Frequency Response [- 10dB]	56Hz - 19KHz
-----------------------------	--------------

Frequency Response [- 3dB]	61Hz - 19KHz
----------------------------	--------------

Max SPL	111dB
---------	-------

Sensitivity	91dB
-------------	------

2 x Class D amplifier

Power (Peak/Rated)	480W (432+48W) / 240W (216+24W)
--------------------	---------------------------------

Crossover	3.5KHz, 24dB/Oct.
-----------	-------------------

EQ	High (2.5KHz, +/- 12 dB); Low (150Hz, +/- 12 dB)
----	--

LEDs	Power On (Green), Clip (Red)
------	------------------------------

Power Requirement	230Vac - 50 Hz
-------------------	----------------

Minimum Power Consumption	120W
---------------------------	------

Power Connector	VDE with T2A-250V Fuse
-----------------	------------------------

Dimensions (WxHxD)	270 x 495 x 270 mm
--------------------	--------------------

Weight	7,2 Kg
--------	--------