

GO-SOUND 10A

480 Watt 10" Polypropylene Active Speaker

Go-Sound series is built with the user in mind. As result of years of experience gathered by Soundsation in portable sound systems, we designed these versatile high-quality speakers with unmatched value and performances. Built in a polypropylene cabinet, sturdy yet compact and lightweight, these active speaker are equipped with Class AB amplifiers, which guarantee reliability and outstanding performances. Mic and line inputs are included to allow the user to connect various audio sources such as microphones, mixers as well as smartphones and tablets.Go-Sound series is an incredible value and the perfect solution in many situations such as parties, presentations, schools, conference and live music, delivering great sound quality, reliability and ease of use.











KEY FEATURES

2-Way Active Speaker

Sturdy polypropylene enclosure yet compact and lightweight

480 Watt class AB power amplifier

10" woofer with 1" compression driver

 $Balanced\ microphone/Line\ inputs\ XLR+{}^{1}\!\!/\!{}^{2}"\ Jack\ and\ line\ inputs\ Stereo\ RCA+Stereo\ Mini\ jack\ ideal\ to\ connect\ smartphones\ and\ tablets$

XLR line output

Mic/line switch, volume and equalizer (Hi and Low) controls

36 mm standard pole mount

2 side handles and 1 top handle for convenient carrying

Speaker Dimension (WxHxD) 320 x 490 x 260 mm

Weight 6,4 Kg

MORE SPECIFICATIONS

2-Way active speaker

Woofer	10" with 1.5" voice coil
Compression driver	1" voice coil, 1" throat
Directivity	90° x 50°, asymmetric
Frequency Response [- 3dB]	75Hz - 18KHz
Frequency Response [- 10dB]	70Hz - 18KHz
Max SPL(Peak)	112 dB
Sensitivity	93dB
Class AB amplifier	
Power (Peak/Rated)	480W/240W
Crossover	3.2KHz, 18dB/Oct.
EQ	High (2.5KHz, +/- 12 dB); Low (150Hz, +/- 12 dB)
LEDs	Power On (Green), Clip (Red)
Power Requirement	230Vac - 50 Hz
Minimum Power Consumption	130W
Power Connector	VDE with T1A-250V Fuse
Speaker Dimension (WxHxD)	320 x 490 x 260 mm
Weight	6,4 Kg

