

## HYPER BASS 15P

15" Bass-Reflef Professional Passive Subwoofer

HYPER BASS 15P is a passive subwoofer with bass-reflex, compact, lightweight and very easy to use. It is ideal for both fixed installations and live music events or PA in general. HYPER BASS 15P has a program power of 1200W (2400W peak) with a 15" professional custom woofer. This model has a sturdy, lightweight and elegant plywood housing with metal grille and acoustic foam to protect the transducers inside and give an attractive appearance. It also has 2 recessed handles (1 on each side) and a standard M20 mounting hole to allow any type of installation with SUBEST100-BK or SUBST100-M20 poles.





## **KEY FEATURES**

Sturdy housing in plywood with front bass-reflex

Anti-scratch powder coating

15" csutom woofer with 4" voice coil

**Power** 600W RMS - 80hm (1200W Program / 2400W Peak)

**Connection** Spekon Input and Output (+1 Positive, -1)

Recessed handles (1 per side)

Pole mounting with M20 thread





## **MORE SPECIFICATIONS**

| Frequency Resp. (-10 dB)     | 35Hz - 1KHz                             |
|------------------------------|---|
| Frequency Resp. (-3 dB)      | 45Hz - 600Hz                            |
| Sensitivity (1W @ 1m)        | 96dB                                    |
| MAX SPL                      | 127dB                                   |
| RMS Power                    | 600W                                    |
| Program/Peak Power           | 1200/2400W                              |
| Impedance                    | 8 Ohm                                   |
| LF Diameter                  | 15"                                     |
| LF Voice Coil                | 4"                                      |
| Input Connectors             | 1x2 Poles Speakon connector             |
| Output Connectors            | 1x2 Poles Speakon connector             |
| <b>Housing Material</b>      | Plywood                                 |
| Grille Material              | Steel                                   |
| Thickness Grille             | 1.5mm                                   |
| Handles                      | 2 Recessed handles (1 on each side)     |
| Pole Mount                   | SUBEST100-BK or SUBST100-M20 (Optional) |
| Subwoofer Dimensions (WxHxD) | 460 x 610 x 565 mm                      |
| Packing Dimensions (WxHxD)   | 545 x 720 x 640 mm                      |
| Subwoofer Weight             | 32,5 kg                                 |
| Packing Weight               | 37,6 kg                                 |

